

Code: S1108A

## VIDEO DOORPHONE **S1108A** VIDOS

Net: **227.04 EUR** Gross: **227.04 EUR**



Video Doorphone is mounted in a surface housing. The S1108A is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.

### SPECIFICATION

|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compatibility:                    | VIDOS DUO                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Sensor:                           | 1/2.7 " Fish Eye CMOS, 2 Mpx                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| View angle:                       | 170 °                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| IR illuminator:                   | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| LED illuminator:                  | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| proximity reader built-in:        | Standard : Unique EM 125kHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Built-in keypad:                  | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| The number of subscribers served: | 8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Video output:                     | compatible with the VIDOS DUO digital video doorphone system                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Main features:                    | <ul style="list-style-type: none"><li>• Wiring - 2 wires without polarity</li><li>• Relay output : 1 pcs or 2 pcs - B5 module</li><li>• Permanent or cyclical zoom-up of the observed image</li><li>• Electric strikes and electromagnetic locks support</li><li>• Electric lock supply: 12V DC / max. 300mA</li><li>• Easy to add and delete users via MASTER key fobs</li><li>• Call start and lock opening indicator</li><li>• Built-in information signboard module with backlight</li></ul> |
| Power supply:                     | 24 V DC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Power consumption:                | ≤ 4.8 W (operation)<br>≤ 1.2 W (Standby mode)                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Housing:                          | Acid-proof steel / Plastic, Waterproof                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Color:                            | Silver                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                        |                   |
|------------------------|-------------------|
| "Index of Protection": | IP54              |
| Operation temp:        | -20 °C ... 55 °C  |
| Weight:                | 0.98 kg           |
| Dimensions:            | 281 x 110 x 44 mm |
| Manufacturer / Brand:  | VIDOS             |
| Guarantee:             | <b>3 years</b>    |

## PRESENTATION

Front panel:



Side view:





Mounting side view:



Connectors view:



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm

Gross Weight: 0 kg