

Code: S1600

VIDEO DOORPHONE **S1600** VIDOS

Net: **382.39 EUR** Gross: **382.39 EUR**

Video Doorphone is mounted in a surface housing. The S1600 is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.



SPECIFICATION

Compatibility:	VIDOS DUO
Sensor:	1/2.7 " Fish Eye CMOS, 600 TVL
View angle:	105 °
IR illuminator:	—
LED illuminator:	✓
proximity reader built-in:	Standard : Unique EM 125kHz
Built-in keypad:	✓
The number of subscribers served:	max. 256 or max. 6368 - depending on the type of modules used
Video output:	compatible with the VIDOS DUO digital video doorphone system
Main features:	• Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 module • Touch and backlit keyboard buttons • Connector for the additional exit button • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 280mA • DIP SWITCH for configuration and addressing • Window with device operation status indicators • Built-in multifunctional LCD performing the function of an electronic list of tenants and an information panel • Programming via the keyboard • microSD socket
Power supply:	26 V DC

Power consumption:	≤ 5 W (operation) ≤ 1 W (Standby mode)
Housing:	Acid-proof steel / Plastic, Waterproof
Color:	Silver
"Index of Protection":	IP54
Operation temp:	-20 °C ... 55 °C
Supported languages:	Polish
Weight:	1.82 kg
Dimensions:	355 x 135 x 80 mm
Manufacturer / Brand:	VIDOS
Guarantee:	3 years

PRESENTATION

Front view:



Rear view:






Internal view of the housing:



Connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------