

Code: S1532A

## VIDEO DOORPHONE **S1532A** VIDOS

Net: **358.49 EUR** Gross: **358.49 EUR**

Video Doorphone is mounted in a flush-mounted housing. The S1532A is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.



### SPECIFICATION

|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compatibility:                    | VIDOS DUO                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Sensor:                           | 1/2.7 " Fish Eye CMOS, 600 TVL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| View angle:                       | 105 °                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| IR illuminator:                   | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| LED illuminator:                  | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| proximity reader built-in:        | Standard : Unique EM 125kHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Built-in keypad:                  | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| The number of subscribers served: | 32                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Video output:                     | compatible with the VIDOS DUO digital video doorphone system                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Main features:                    | <ul style="list-style-type: none"><li>• Fisheye lens</li><li>• Wiring - 2 wires without polarity</li><li>• Relay output : 1 pcs or 2 pcs - B5 module</li><li>• Connector for the additional exit button</li><li>• Electric strikes and electromagnetic locks support</li><li>• Electric lock supply: 12V DC / max. 280mA</li><li>• DIP SWITCH for configuration and addressing</li><li>• Window with device operation status indicators</li><li>• Illuminated buttons and signboards for the surnames</li></ul> |
| Power supply:                     | 26 V DC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Power consumption:                | ≤ 5 W (operation)<br>≤ 1 W (Standby mode)                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Housing:                          | Acid-proof steel / Plastic, Waterproof                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

|                        |                   |
|------------------------|-------------------|
| Color:                 | Silver            |
| "Index of Protection": | IP54              |
| Operation temp:        | -20 °C ... 55 °C  |
| Weight:                | 2.07 kg           |
| Dimensions:            | 316 x 256 x 48 mm |
| Manufacturer / Brand:  | VIDOS             |
| Guarantee:             | <b>3 years</b>    |

## PRESENTATION

Front view:



Mounting side view:



Internal view, after remove the cover:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60