

Code: DS-2DE3A400BW-DE(F1)(T5)

IP SPEED DOME CAMERA OUTDOOR **DS-2DE3A400BW-DE(F1)(T5)**

ACUSENSE 3.7 Mpx 4 mm Hikvision

Net: **396.06 EUR** Gross: **396.06 EUR**

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install.

For a few models of IP cameras working at $\geq 1920 \times 1080$ resolution we recommend to use of network with 1Gb/s bandwidth.

Camera from AcuSense series.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/1.8 " Progressive Scan CMOS
Matrix size:	4 Mpx
Resolution:	2560 x 1440 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens:	4 mm
View angle:	89 °
Optical zoom:	—
Digital zoom:	x 16
Range of IR illumination:	—
White light LED illuminator range:	30 m
S/N ratio:	> 52 dB
Video output:	—
Preset rotation speed:	60 °/s (horizontal) 50 °/s (vertical)
Rotation speed (manual control):	0.1 °/s ... 60 °/s (horizontal) 0.1 °/s ... 50 °/s (vertical)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Horizontal rotation range:	350 ° - Rotation of the head is limited by stops
Vertical rotation range:	0 ° ... 90 °
RS-485 interface:	—
Number of presets:	300
Horizontal scan:	✓
Route settings:	8
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	1 / 1
Audio:	• External microphone input, • Audio output • Speaker built-in • Audio detection • Bi-directional audio streaming support • Noise reduction
Main stream frame rate:	25 fps @ 3.7 Mpx
Network interface:	10/100 Base-TX (RJ-45)
WEB Server:	Built-in, NVR compliance
Max. number of on-line users:	20
ONVIF:	✓
Memory card slot:	Micro SD memory cards up to 512GB support (possible local recording)
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Main features:	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Intelligent 3D Positioning System • Configurable Privacy Zones - 24 • Motion Detection • Sharpness - sharper image outlines • Configurable: brightness, contrast, saturation • AGC - Automatic Gain Control • Auto White Balance • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • NAS - Network Attached Storage support • Intelligent Image Analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, classification of people and vehicles, abandoned/missing object, face detection - advanced face capture features - detection of up to 5 faces simultaneously
Power supply:	• PoE (802.3at), • 12 V DC / 3.33 A (power adapter included)



Power consumption:	≤ 14 W
Housing:	Speed Dome, Plastic
Color:	White + Black
Operation temp:	-30 °C ... 65 °C
"Index of Protection":	IP66
Weight:	1.13 kg
Dimensions:	179 x 120 x 182 mm
Supported languages:	Polish, English
Manufacturer / Brand:	Hikvision
SAP Code:	327000671
Guarantee:	3 years

PRESENTATION


Bottom view:



Memory card slot and "Reset" button:



Camera connectors:




Connectors description:



Camera dimensions:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------