

Code: APS-412/IT

BUFFERED SWITCHING POWER SUPPLY ADAPTER **APS-412/IT** SATEL

Net: **187.21 EUR** Gross: **187.21 EUR**

The buffered power supply adapter is designed to powering control panels, sensors, code locks, cameras, consoles, intercoms and other alarm system equipment. The APS-412/IT has a special connector that enables cooperation with Satel devices.



SPECIFICATION

Adapter type:	Switching
Input voltage:	230 V AC
Output voltage:	12 V DC
Max. output current (total):	4 A
Power:	48 W
Battery charging current:	0.5 A / 1 A
Protections:	• Short-circuit • Reverse polarity connection • Overload • Overvoltage
Adapter operation control:	• DC output voltage presence indication • Battery charging indication • AC input voltage presence indication • WS output - indicating AC power collapse • WB output - Low battery voltage • WP output Current overload indication
Housing type:	Plastic, DIN, TS-35 rail mounting
Weight:	0.28 kg
Dimensions:	79 x 123 x 60 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION

Adapter connectors:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Side view:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------