

Code: DS-KD-DIS

DISPLAY MODULE **DS-KD-DIS** Hikvision

Net: **130.56 EUR** Gross: **130.56 EUR**

The DS-KD-DIS module is designed to work with the DS-KD8003-IME1 or DS-KD8003-IME2 video doorphone module. The device allows calling an indoor station from the contacts list presented on the display. The DS-KD-DIS also allows to display numbers dialed using the DS-KD-KP keypad and information about the connection itself.

Installation of DS-KD-xx series modules takes place in dedicated DS-KD-ACF series housings (flush-mounted housings) and DS-KD-ACW series housings (surface-mounted housings). The masking frames attached to the housings of both series are made of aluminum.



SPECIFICATION

Compatibility:	DS-KD8003-IME1, DS-KD8003-IME2
Display:	3.5 " TFT LCD, 320 x 480 px
Main features:	• You can add up to 500 contacts to the device • Calling the indoor station from the contacts list displayed on the device • Displaying the number of the indoor station entered using the DS-KD-KP keypad module • Displaying information about the duration of a call, opening the door, entering the door station into the mode of recording messages after a missed call • Illuminated buttons - 4 pcs • RS-485 interface
Power supply:	Supplied by DS-KD8003-IME1 or DS-KD8003-IME2
Power consumption:	≤ 3 W
Permissible relative humidity:	10 ... 95 % (non-condensing)
"Index of Protection":	IP65
Housing:	Plastic
Color:	Black
Operation temp:	-20 °C ... 60 °C
Weight:	0.24 kg
Dimensions:	100 x 98 x 34 mm
Manufacturer / Brand:	Hikvision
SAP Code:	305301210

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Guarantee:

3 years

PRESENTATION

Front panel:



Rear view:







Connectors:



Dimensions:



Example of application:



1. Alarm sensors
2. Indoor panel
3. Switch PoE
4. Guard station
5. Main unit powered by PoE switch
6. IP cameras
7. Expansion modules

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------