

Code: BCS-EA25FSR3-G(H2)

AHD, HD-CVI, HD-TVI, PAL CAMERA **BCS-EA25FSR3-G(H2)** - 5 Mpx 2.8 mm

Net: **46.10 EUR** Gross: **46.10 EUR**

Megapixel camera with 1/2.8" STARVIS™ CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.



SPECIFICATION

Standard:	AHD / HD-CVI / HD-TVI / CVBS
Resolution:	• 2704 x 1950 - 5 Mpx @ AHD / HD-TVI - 20 fps • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI - 25 fps • 960 x 576 - 960H @ PAL
Sensor:	1/2.8 " STARVIS™ CMOS
Lens:	2.8 mm
View angle:	103 °
Range of IR illumination:	30 m
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio:	• Microphone built-in • Audio output
OSD menu:	✓
Main features:	• D-WDR - Wide Dynamic Range • Auto White Balance • AGC - Automatic Gain Control • 3D-DNR - Digital Noise Reduction • Day/night mode • ICR - Movable InfraRed filter
Power supply:	12 V DC / 416 mA
Power consumption:	< 5 W
Housing:	Dome, Metal
Color:	Graphite
"Index of Protection":	IP66
Mechanical protection class:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation temp:	-20 °C ... 60 °C
Weight:	0.3 kg
Dimensions:	Ø 94 x 80 mm
Supported languages:	Polish, English
Manufacturer / Brand:	BCS UNIVERSAL
Guarantee:	3 years

PRESENTATION

Camera is out from clamping ring:



Dimensions:



Configuration switches:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------