

Code: BCS-EA58VSR4-G(H2)

AHD, HD-CVI, HD-TVI, PAL CAMERA **BCS-EA58VSR4-G(H2)** - 8 Mpx, 4K
UHD 3.6 ... 10 mm - MOTOZOOM
Net: **111.26 EUR** Gross: **111.26 EUR**

Megapixel camera with 1/1.8" CMOS sensor and AHD / HD-CVI / HD-TVI / CVBS.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.



SPECIFICATION

Standard:	AHD / HD-CVI / HD-TVI / CVBS
Resolution:	3840 x 2160 - 8 Mpx, 4K UHD @ AHD / HD-TVI / HD-CVI, 15 fps , 960 x 576 - 960H @ CVBS
Sensor:	1/1.8 " CMOS
Lens:	3.6 ... 10 mm - Motozoom
View angle:	123 ° ... 48 °
Range of IR illumination:	40 m
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio:	Microphone built-in
OSD menu:	✓
Main features:	• D-WDR - Wide Dynamic Range • Auto White Balance • AGC - Automatic Gain Control • Day/night mode • ICR - Movable InfraRed filter
Power supply:	12 V DC / 840 mA
Power consumption:	< 10 W
Housing:	Dome, Metal
Color:	Graphite
"Index of Protection":	IP66
Mechanical protection class:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


Operation temp:	-20 °C ... 60 °C
Weight:	0.5 kg
Dimensions:	Ø 119 x 98 mm
Supported languages:	Polish, English
Manufacturer / Brand:	BCS UNIVERSAL
Guarantee:	3 years

PRESENTATION

Camera is out from clamping ring:



Dimensions:



Configuration switches:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------