

Code: PROTECT-C360

AHD MOBILE CAMERA **PROTECT-C360** - 1080p 3.6 mm

Net: **57.54 EUR** Gross: **57.54 EUR**

The PROTECT-C360 camera is designed for installation outside vehicles.

The AHD interface allows to transmission of analog, composite video signal via coaxial cable. During transmission there are no delays and is maintained the original, high quality image.

Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image. Camera is according to IP69 Index of Protection norm.



SPECIFICATION

Standard:	AHD
Sensor:	1/2.9 " Sony CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	3.6 mm
View angle:	110 °
Range of IR illumination:	15 m
Video output:	1 Vpp / 75 Ω - M12, 4-pin socket, Code A
Audio:	—
Main features:	• ICR filter - IR illuminators support • Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image • Rotating body
OSD menu:	—
Housing:	Metal
Color:	Black
"Index of Protection":	IP69
Application:	The camera is designed for installation outside vehicles
Power supply:	12 V DC / 250 mA - Powering the cameras with 12V DC voltage directly from recorder


Power consumption:	3 W
Operation temp:	-20 °C ... 50 °C
Length of the cable:	0.4 m
Weight:	0.28 kg
Dimensions:	90 x 77 x 63 mm
Guarantee:	2 years

PRESENTATION

Camera is out from clamping ring:



Mounting side view:



In the kit:



OUR OPINIONS



- Solid workmanship.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60