

Code: DS-2XM6522G0-IM/ND(4mm)(C)

IP MOBILE CAMERA **DS-2XM6522G0-IM/ND(4mm)(C)** - 1080p 4.0 mm

Hikvision

Net: **361.38 EUR** Gross: **361.38 EUR**

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

Extremely robust camera construction, appropriate shape, excellent IP68 degree of protection and the highest class of mechanical strength IK10 allow the camera to work even in very difficult conditions (eg assembly on the vehicle's body).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. The connection cable has been terminated with the M12 connector.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.8 " Progressive Scan CMOS
Scanning system:	Progressive
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens:	4.0 mm
View angle:	• 77 ° (manufacturer data) • 74 ° (our tests result)
Compression:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination:	10 m
Alarm inputs / outputs:	—
Audio:	—
Memory card slot:	—
Main stream frame rate:	25 fps @ 1080p
Network interface:	10/100 Base-TX, M12, 4-pin socket - code D
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, Bonjour
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	✓
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect

Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
RS-485 interface:	—
Main features:	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • HLC - High Light Compensation (spot) • BLC - Back Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Configurable Privacy Zones • Lens focus loss detection • The device has a built-in heater • Intelligent Image Analysis : Motion Detection, intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, abandoned/missing object, scene changing, face detection
Power supply:	PoE (802.3af)
Power consumption:	≤ 8.8 W
Housing:	Compact, Aluminum
Color:	Black
Vandal-proof:	IK10
"Index of Protection":	IP68
Operation temp:	-40 °C ... 70 °C
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Weight:	0.88 kg
Dimensions:	164 x 123 x 65 mm
Manufacturer / Brand:	Hikvision
SAP Code:	316400111
Guarantee:	3 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60




Side view:



Camera mounting side view:



Camera dimensions:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------