

Code: VT03211D-P2-S2

VIDEO DOORPHONE **VT03211D-P2-S2** DAHUA

Net: **296.59 EUR** Gross: **296.59 EUR**

The device works with video doorphones, and other DAHUA panels. Video Doorphone is mounted in a surface housing.



SPECIFICATION

Compatibility:	DAHUA
Sensor:	1/2.8 ", 2 Mpx CMOS
View angle:	129 °
Image compression method:	H.264
Resolution:	• Main stream : 800 x 480, 1280 x 720, 720 x 576 • Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240
IR illuminator:	✓
proximity reader built-in:	Access control cards - 13.56 MHz S50
The number of subscribers served:	2
Main features:	• The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Echo suppression and reduction / digital noise reduction, • Tamper detection - opening the enclosure, • Vandal-proof front panel, • Output for the additional lock release button, • WDR - 120 dB - Wide Dynamic Range, • Motion Detection
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS

Power supply:	• PoE (802.3af), • 12 V DC / 1 A
Power consumption:	≤ 7 W (operation) ≤ 1 W (Standby mode)
Housing:	Aluminum alloy, Waterproof
Color:	Graphite
"Index of Protection":	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
Mechanical strength:	IK08
Operation temp:	-30 °C ... 60 °C
Weight:	0.48 kg
Dimensions:	182 x 101 x 32 mm
Supported languages:	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Front view:



Side view:



Rear view:



Connectors view:



Connection schematic diagram:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------