

Code: DS-KV8113-WME1(B)/SU

# WIRELESS VIDEO DOORPHONE **DS-KV8113-WME1(B)/SU** Wi-Fi / IP

## Hikvision

Net: **240.58 EUR** Gross: **240.58 EUR**

Wi-Fi / IP video doorphone is dedicated to work with II generation IP Hikvision internal panels.

Video Doorphone is mounted in a surface housing.



### SPECIFICATION

|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| Sensor:                      | 2 Mpx                                                                      |
| Resolution:                  | 1920 x 1080                                                                |
| Camera view angle:           | 129 °                                                                      |
| IR illuminator:              | ✓                                                                          |
| LED illuminator:             | —                                                                          |
| PIR detector:                | —                                                                          |
| Doorbell button:             | 1 pcs                                                                      |
| proximity reader built-in:   | 13.56 MHz S50                                                              |
| Wireless transmission range: | The range limited only by the availability of the Wi-Fi network            |
| Wi-Fi standard:              | IEEE 802.11b / IEEE 802.11g / IEEE 802.11n                                 |
| Network interface:           | <ul style="list-style-type: none"><li>• Ethernet</li><li>• Wi-Fi</li></ul> |
| RS-485 interface:            | ✓                                                                          |
| Video output:                | —                                                                          |
| Video format:                | H.264                                                                      |
| Supported audio formats:     | G.711                                                                      |
| Alarm inputs:                | 4 pcs                                                                      |

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:         | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• BLC - Back Light Compensation</li> <li>• Bidirectional communication,</li> <li>• Full support via network : WiFi / LAN,</li> <li>• Tamper detection - removing from mounting surface</li> <li>• Video Doorphone is mounted in a surface housing</li> <li>• The device has the ability to work with the <a href="#">Hik-Connect</a> application for mobile devices, without the use of an internal panel</li> <li>• IK rating : IK08</li> </ul> |
| Power supply:          | <ul style="list-style-type: none"> <li>• PoE (802.3af)</li> <li>• 12 V DC / 830 mA (max)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Power consumption:     | < 10 W (operation)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Housing:               | Aluminum + Plastic, Protects against weather conditions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Mount:                 | Surface-mounted                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Color:                 | Black + Gray                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| "Index of Protection": | IP65                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Operation temp:        | -40 °C ... 53 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Weight:                | 0.38 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Dimensions:            | 174 x 91 x 30 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Supported languages:   | Polish, English, Bulgarian, Croatian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian                                                                                                                                                                                                                                                                                                                                                                                                       |
| Manufacturer / Brand:  | Hikvision                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| SAP Code:              | 305302344                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Guarantee:             | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## PRESENTATION

Front panel:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Internal view (after open the enclosure):



Connectors:



Memory card slot:



In the kit:



## OUR OPINIONS



- o Very easy installation.

## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60