

Code: BAT-RECHARGE/X4

CHARGER **BAT-RECHARGE/X4** XTAR

Net: **35.94 EUR** Gross: **35.94 EUR**

The BAT-RECHARGE/X4 Charger is the versatile device for many types of batteries.

Supports protected PCM/PCB batteries in sizes 20700/21700. The LCD display informs about the charging capacity, cell voltage, charging current and percentage of battery charge.



SPECIFICATION

Battery type:	• Li-Ion 3.6 / 3.7 V - ICR / IMR / INR, 14500, 14650, 16340, 17335, 17500, 17670, 18350, 18490, 18500, 18650, 18700, 20700, 21700, 22650, 25500, 26650, • Ni-MH, Ni-Cd 1.2 V - AAAA / AAA / AA / A / C
Battery charging current:	0.5 A @ 4 pcs , 1 A @ 4 pcs , 2 A @ 2 pcs
LED indicator:	—
LCD display:	✓
Main features:	• The LCD display informs about the charging capacity, cell voltage, charging current and percentage of battery charge, • Supports protected PCM/PCB batteries in sizes 20700/21700, • Deeply discharged cell reactivation function, • Power Bank (5V, max. 1A) function • Charging Li-ion batteries controlled by a three-stage processor TC/CC/CV charging process • charging Ni-MH batteries with the CC method • 4 independent charging channels • End of charge voltage : 4.2 V @ Li-Ion, 1.45 V @ NiMH • Short-circuit protection • Protection against reverse polarity connection • Overload protection • Overvoltage protection • Overcharge protection
Power supply:	• 100 V ... 240 V AC • 5 V DC / 2.1 A @ Micro USB-B socket (power adapter not included)
Weight:	0.27 kg
Dimensions:	• 118 x 143 x 38 mm • Power cord : 120 cm
Manufacturer / Brand:	XTAR
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front view:



Connectors:



In the kit:



OUR OPINIONS



- It gives fast, safe batteries charging.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------