

Code: UT-132B

UNIVERSAL METER **UT-132B** UNI-T

Net: **15.53 EUR** Gross: **15.53 EUR**

UT-132B is a universal digital meter used to measure: voltage, current, resistance. The device also has a built-in battery tester.



SPECIFICATION

DC voltage measurement:	200 mV $\pm$ (0.5% + 2) @ 0.1 mV , 2 V $\pm$ (0.5% + 2) @ 1 mV , 20 V $\pm$ (0.5% + 2) @ 10 mV , 200 V $\pm$ (0.5% + 2) @ 100 mV , 600 V $\pm$ (0.8% + 2) @ 1 V
AC voltage measurement:	200 V $\pm$ (1.2% + 3) @ 0.1 mV : 45 Hz ... 400 Hz , 600 V $\pm$ (1.2% + 3) @ 1 mV : 45 Hz ... 400 Hz
DC current measurement:	2000 μ A $\pm$ (1% + 2) @ 1 μ A , 200 mA $\pm$ (1% + 2) @ 0.1 mA , 10 A $\pm$ (2% + 5) @ 0.01 A
AC current measurement:	—
Resistance measurement:	200 Ω $\pm$ (0.8% + 5) @ 0.1 Ω , 2 k Ω $\pm$ (0.8% + 5) @ 1 Ω , 20 k Ω $\pm$ (0.8% + 5) @ 10 Ω , 200 k Ω $\pm$ (0.8% + 5) @ 100 Ω , 2 M Ω $\pm$ (0.8% + 5) @ 1 k Ω , 20 M Ω $\pm$ (1% + 5) @ 10 k Ω
Capacitance measurement:	—
Inductance measurement:	—
Frequency measurement:	—
Square-wave signal duty ratio measurement:	—
Temperature measurement:	—
Automatic change of measuring ranges:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

hFE:	✓
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	• Measurement of the battery discharge level: 9V, 1.5V, • Hold - stopping the meter reading, • LCD display, • Aesthetic and solid construction, • Low battery level alarm
Power supply:	9V, type 6F22 battery - included
Weight:	0.2 kg
Dimensions:	140 x 74 x 38 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



Rear view:



Place for 9V battery:



Included, among others measuring adapter:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------