

Code: UT-191T

UNIVERSAL METER **UT-191T** UNI-T

Net: **94.33 EUR** Gross: **94.33 EUR**

The UT-191T is a universal digital meter used to measure: voltage, current, resistance, capacity, frequency, temperature and checking the correct operation of diodes. The meter has the function of automatic change of measuring ranges, as well as the relative measurement mode.

The device meets the IP65 tightness class.



SPECIFICATION

DC voltage measurement:	$600\text{ mV} \pm (0.7\% + 3)$ @ 0.1 mV , $6\text{ V} \pm (0.5\% + 3)$ @ 0.001 V , $60\text{ V} \pm (0.7\% + 3)$ @ 0.01 V , $600\text{ V} \pm (0.7\% + 3)$ @ 0.1 V
AC voltage measurement:	$600\text{ mV} \pm (1.0\% + 4)$ @ 0.1 mV , $6\text{ V} \pm (0.7\% + 3)$ @ 0.001 V , $60\text{ V} \pm (1.0\% + 3)$ @ 0.01 V , $600\text{ V} \pm (1.0\% + 3)$ @ 0.1 V • LPF mode : $600\text{ V} \pm (2.0\% + 5)$ @ 0.1 V • LoZ mode : $600\text{ V} \pm (2.0\% + 5)$ @ 0.1 V
DC current measurement:	$600\text{ }\mu\text{A} \pm (0.8\% + 3)$ @ $0.1\text{ }\mu\text{A}$, $6000\text{ }\mu\text{A} \pm (0.8\% + 3)$ @ $1\text{ }\mu\text{A}$, $60\text{ mA} \pm (0.8\% + 3)$ @ 0.01 mA , $600\text{ mA} \pm (0.8\% + 3)$ @ 0.1 mA , $6\text{ A} \pm (1.0\% + 3)$ @ 0.001 A , $20\text{ A} \pm (1.2\% + 5)$ @ 0.01 A
AC current measurement:	$600\text{ }\mu\text{A} \pm (1.0\% + 3)$ @ $0.1\text{ }\mu\text{A}$, $6000\text{ }\mu\text{A} \pm (1.0\% + 3)$ @ $1\text{ }\mu\text{A}$, $60\text{ mA} \pm (1.0\% + 3)$ @ 0.01 mA , $600\text{ mA} \pm (1.0\% + 3)$ @ 0.1 mA , $6\text{ A} \pm (1.2\% + 3)$ @ 0.001 A , $20\text{ A} \pm (1.5\% + 5)$ @ 0.01 A

Resistance measurement:	$600\ \Omega \pm (1.0\% + 2)\ @\ 0.1\ \Omega$, $6\ k\Omega \pm (0.8\% + 2)\ @\ 0.001\ k\Omega$, $60\ k\Omega \pm (0.8\% + 2)\ @\ 0.01\ k\Omega$, $600\ k\Omega \pm (0.8\% + 2)\ @\ 0.1\ k\Omega$, $6\ M\Omega \pm (1.2\% + 3)\ @\ 0.001\ M\Omega$, $60\ M\Omega \pm (2.5\% + 5)\ @\ 0.01\ M\Omega$
Capacitance measurement:	$6\ nF \pm (4\% + 8) + \text{capacity of test leads @ } 1\ pF$, $60\ nF \dots 600\ \mu F \pm (3\% + 5)\ @\ 10\ pF \dots 100\ nF$, $6\ mF \dots 60\ mF \pm 10\% \ @\ 1\ \mu F \dots 10\ \mu F$
Inductance measurement:	—
Frequency measurement:	$10\ Hz \dots 1\ MHz \pm (0.1\% + 4)\ @\ 0.01\ Hz \dots 0.001\ MHz$
Square-wave signal duty ratio measurement:	$0.1\ \% \dots 99.9\ \% \pm (2\% + 5)\ @\ 0.1\ \%$
Temperature measurement:	• °C $-40 \dots 400\ ^\circ C \pm (1\% + 2^\circ C)\ @\ 0.1\ ^\circ C \dots 1\ ^\circ C$, • °F $-40 \dots 752\ ^\circ F \pm (1\% + 4^\circ F)\ @\ 0.2\ ^\circ F \dots 2\ ^\circ F$
Automatic change of measuring ranges:	✓
hFE:	—
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
USB:	—
Main features:	• True RMS - accurate measurement of the RMS current and voltage for any waveform, • Possibility to measure AC voltage using low measuring impedance (LoZ mode), • LPF function - allows to measure the AC voltage values using low-pass filter with a frequency limit of 200 Hz, • Robust housing that meets the requirements of the IP65 "Index of Protection" class, • Freezing the last reading, • Flashlight built-in, • Freezing the highest or lowest measurement, • REL - relative measurement mode, • Analog bargraph, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case
Power supply:	9V, type 6LR61 battery
Weight:	0.4 kg
Dimensions:	180 x 87 x 66 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Rear view:



Place for 9V battery:



In the kit:



Device is secured by handy case:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------