

Frequency measurement:	99.99 Hz $\pm$ (0.5% + 3) @ 0.01 Hz 999.9 Hz $\pm$ (0.5% + 3) @ 0.1 Hz , 9.999 kHz $\pm$ (0.5% + 3) @ 0.001 kHz , 99.99 kHz $\pm$ (0.5% + 3) @ 0.01 kHz , 1 % ... 99.9 % @ 0.1 %
Temperature measurement:	—
Automatic change of measuring ranges:	✓
hFE:	—
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
USB:	—
Main features:	• Hold - stopping the meter reading, • REL - relative measurement mode, • Large, readable LCD display, • Low battery indicator, • Aesthetic and solid construction, • Automatic shutdown after 30 minutes of inactivity
Power supply:	CR2032 lithium battery - included
Weight:	0.08 kg
Dimensions:	110 x 58 x 13 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION



The product has a very small dimensions:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Internal view of the housing:



In the kit:



Device is secured by handy case:



OUR OPINIONS



- Very small dimensions of the device.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------