

Code: UT-120A

UNIVERSAL METER **UT-120A** UNI-T

Net: **19.22 EUR** Gross: **19.22 EUR**

UT-120A is a universal digital meter used to measure: voltage, resistance, diodes, continuity, frequency, duty cycle factor.



SPECIFICATION

DC voltage measurement:	4 V $\pm$ (0.8% + 1) @ 0.001 V , 40 V $\pm$ (0.8% + 1) @ 0.01 V , 400 V $\pm$ (0.8% + 1) @ 0.1 V , 600 V $\pm$ (1.0% + 3) @ 1 V
AC voltage measurement:	4 V $\pm$ (1.2% + 3) @ 0.001 V , 40 V $\pm$ (1.2% + 3) @ 0.01 V , 400 V $\pm$ (1.2% + 3) @ 0.1 V , 600 V $\pm$ (1.5% + 5) @ 1 V
DC current measurement:	—
AC current measurement:	—
Resistance measurement:	400 Ω $\pm$ (1.2% + 2) @ 0.1 Ω , 4 k Ω $\pm$ (1.0% + 2) @ 0.001 k Ω , 40 k Ω $\pm$ (1.0% + 2) @ 0.01 k Ω , 400 k Ω $\pm$ (1.0% + 2) @ 0.1 k Ω , 4 M Ω $\pm$ (1.2% + 2) @ 0.001 M Ω , 40 M Ω $\pm$ (1.5% + 2) @ 0.01 M Ω
Capacitance measurement:	—
Inductance measurement:	—
Frequency measurement:	99.9 Hz $\pm$ (0.5% + 3) @ 0.1 Hz , 0.999 kHz $\pm$ (0.5% + 3) @ 0.001 kHz , 9.99 kHz $\pm$ (0.5% + 3) @ 0.01 kHz , 99.9 kHz $\pm$ (0.5% + 3) @ 0.1 kHz
Square-wave signal duty ratio measurement:	0.1 ... 99.9 % @ 0.1 %
Temperature measurement:	—
Automatic change of measuring ranges:	✓
hFE:	—
Diode test:	✓

Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	• Large, readable LCD display • Freezing the last reading • Low battery level alarm • Aesthetic and solid construction • The set includes a practical case
Power supply:	1 x CR2032 lithium battery - included
Weight:	0.076 kg
Dimensions:	110 x 58 x 13 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION



The product has a very small dimensions:



Internal view of the housing:



In the kit:



Device is secured by handy case:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

