

Code: UT-131D

UNIVERSAL METER **UT-131D** UNI-T

Net: 16.28 EUR Gross: 16.28 EUR



The UT-131D is a universal digital meter used to measure: voltage, current, resistance, diodes.

SPECIFICATION

DC voltage measurement:	200 mV ± (0.7% + 3) @ 0.1 mV , 2000 mV ± (0.5% + 2) @ 1 mV , 20 V ± (0.7% + 3) @ 0.01 V , 200 V ± (0.7% + 3) @ 0.1 V , 250 V ± (0.7% + 3) @ 1 V
AC voltage measurement:	200 V ± (1.2% + 3) @ 0.1 V , 250 V ± (1.2% + 3) @ 1 V
DC current measurement:	2000 μA ± (1.0% + 2) @ 1 μA , 20 mA ± (1.0% + 2) @ 0.01 mA , 200 mA ± (1.0% + 2) @ 0.1 mA , 10 A ± (1.2% + 5) @ 0.01 A
AC current measurement:	—
Resistance measurement:	200 Ω ± (1.0% + 2) @ 0.1 Ω , 2 kΩ ± (0.8% + 2) @ 0.001 kΩ , 20 kΩ ± (0.8% + 2) @ 0.01 kΩ , 200 kΩ ± (0.8% + 2) @ 0.1 kΩ , 20 MΩ ± (1.2% + 3) @ 0.01 MΩ , 200 MΩ ± (5.0% + 10) @ 0.1 MΩ
Capacitance measurement:	—
Inductance measurement:	—
Frequency measurement:	—
Temperature measurement:	—
Automatic change of measuring ranges:	—
hFE:	—



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	• NCV - electric field detection function • Large, readable LCD display with backlight • Hold - stopping the meter reading • Low battery indicator • Aesthetic and solid construction
Power supply:	2 x 1.5V, type AAA/LR03 battery - included
Weight:	0.21 kg
Dimensions:	134 x 77 x 47 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



Rear view:



Place for batteries 2 x 1.5V AAA:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

