

Code: UT-202A

CLAMP METER **UT-202A** UNI-T

Net: **20.41 EUR** Gross: **20.41 EUR**

The UT-202A is a universal digital meter equipped with clamps enabling the measurement of high currents. The device measures: voltage, current and resistance.



SPECIFICATION

DC voltage measurement:	200 mV $\pm$ (0.8% + 3) @ 0.1 mV , 2 V $\pm$ (0.8% + 1) @ 0.001 V , 20 V $\pm$ (0.8% + 1) @ 0.01 V , 200 V $\pm$ (0.8% + 1) @ 0.1 V , 600 V $\pm$ (1.0% + 3) @ 1 V
AC voltage measurement:	2 V $\pm$ (1.2% + 5) @ 0.001 V , 20 V $\pm$ (1.2% + 5) @ 0.01 V , 200 V $\pm$ (1.2% + 5) @ 0.1 V , 600 V $\pm$ (1.5% + 5) @ 1 V
DC current measurement:	—
AC current measurement:	20 A $\pm$ (2.0% + 5) @ 0.01 A , 200 A $\pm$ (1.5% + 5) @ 0.1 A , 600 A $\pm$ (2.0% + 8) @ 1 A
Resistance measurement:	200 Ω $\pm$ (1.2% + 2) @ 0.1 Ω , 2 k Ω $\pm$ (1.0% + 2) @ 0.001 k Ω , 20 k Ω $\pm$ (1.0% + 2) @ 0.01 k Ω , 200 k Ω $\pm$ (1.0% + 2) @ 0.1 k Ω , 2 M Ω $\pm$ (1.2% + 2) @ 0.001 M Ω , 20 M Ω $\pm$ (1.5% + 2) @ 0.01 M Ω
Capacitance measurement:	—
Inductance measurement:	—
Frequency measurement:	—
Temperature measurement:	—
Automatic change of measuring ranges:	✓
Diode test:	✓
Sound signal of the continuity test:	✓
RS-232:	—

USB:	—
Main features:	• Hold - stopping the meter reading, • Maximum value indication function • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case
Power supply:	9V, type 6LR61 battery - included
Weight:	0.23 kg
Dimensions:	211 x 75 x 28 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



Place for 9V battery:





In the kit:



Device is secured by handy case:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

