

Code: UT-603

METER OF CAPACITANCE, INDUCTANCE AND RESISTANCE UT-603

Net: 53.61 EUR Gross: 53.61 EUR

The UT-603 meter allows you to measure capacitance, inductance, resistance, hFE, and also has the function of checking diodes and circuit continuity.



SPECIFICATION

DC voltage measurement:	—
AC voltage measurement:	—
DC current measurement:	—
AC current measurement:	—
Resistance measurement:	200 $\Omega \pm (0.8\% + 3)$ @ 0.1 Ω , 2 k $\Omega \pm (0.8\% + 1)$ @ 0.001 k Ω , 20 k $\Omega \pm (0.8\% + 1)$ @ 0.01 k Ω , 200 k $\Omega \pm (0.8\% + 1)$ @ 0.1 k Ω , 2 M $\Omega \pm (0.8\% + 1)$ @ 0.001 M Ω , 20 M $\Omega \pm (2.0\%(RD-12) + 5)$ @ 0.01 M Ω , 2000 M Ω @ 1 M Ω - visual measurement
Capacitance measurement:	2 nF $\pm (1\% + 5)$ @ 0.001 nF , 20 nF $\pm (1\% + 5)$ @ 0.01 nF , 200 nF $\pm (1\% + 5)$ @ 0.1 nF , 2 μ F $\pm (4\% + 5)$ @ 0.001 μ F , 20 μ F $\pm (4\% + 5)$ @ 0.01 μ F , 200 μ F $\pm (4\% + 5)$ @ 0.1 μ F , 600 μ F @ 1 μ F - visual measurement
Inductance measurement:	2 mH $\pm (2\% + 8)$ @ 0.001 mH , 20 mH $\pm (2\% + 8)$ @ 0.01 mH , 200 mH $\pm (2\% + 8)$ @ 0.1 mH , 2 H $\pm (5\% + 5)$ @ 0.001 H , 20 H $\pm (5\% + 5)$ @ 0.01 H , 200 H @ 0.1 H - visual measurement
Frequency measurement:	—
Square-wave signal duty ratio measurement:	—

Temperature measurement:	—
hFE:	✓
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	• Large, readable LCD display with backlight • Hold - stopping the meter reading • Aesthetic and solid construction
Power supply:	9V, type 6LR61 battery - included
Weight:	0.29 kg
Dimensions:	172 x 84 x 41 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION



Rear view:



Place for 9V battery:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------