

Code: UT-582+

INSULATION RESISTANCE METER + RCD TESTER **UT-582+** UNI-T

Net: **136.86 EUR** Gross: **136.86 EUR**

The UT-582+ is a digital RCD circuit breaker tester that helps electricians in the diagnosis of electrical installations, thanks to which you can check the voltage and operation of various types of residual current circuit breakers.



SPECIFICATION

AC voltage measurement:	30 V ... 600 V $\pm$ (3% + 3) @ 1 V
Frequency measurement:	45 Hz ... 65 Hz - frequencies displayed are for illustrative purposes
Test of RCDs:	• Working voltage: 220V $\pm$ 10 % • Test current: 10mA / 20mA / 30mA / 100mA / 300mA / 500mA • Switch-off time ranges : - x 1/2 - 10 / 20 / 30 / 100 / 300 / 500 mA @ 2000 ms - x 1 - 10 / 20 / 30 / 100 / 300 mA @ 1000 ms - x 5 - 500 mA @ 300 ms - AUTO RAMP - 10 / 20 / 30 / 100 / 300 / 500 mA @ 300 ms • AUTO RAMP test: measurement of shutdown current (with simultaneous measurement of time)
Automatic change of measuring ranges:	—
RS-232:	—
USB:	—
Main features:	• Phase switch 0° / 180° during RCD test, • Large, readable LCD display with backlight, • Buzzer, • Low battery level alarm, • Aesthetic and solid construction
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	$\leq$ 80 % (non-condensing)
Power supply:	6 x 1.5V, type AA/LR6/FR6 battery - included
Weight:	0.380 kg
Dimensions:	160 x 100 x 69 mm
Manufacturer / Brand:	UNI-T

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Guarantee:

2 years

PRESENTATION

Front panel cover:



Front panel:



Place for batteries 6 x 1.5V AA:



In the kit:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Device is secured by handy case:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------