

Code: PROTECT-LED-KL-1

CONTROL PANEL **PROTECT-LED-KL-1**

Net: **35.85 EUR** Gross: **35.85 EUR**

The PROTECT-LED-KL-1 control panel is used as a monitor of the operating status of the mobile recorder and as an IR remote control extender.



SPECIFICATION

Application:	PROTECT mobile recorders
LED diodes indicating the device operation status:	• PWR - Power supply • REC - Video recording • HDD - Installed and formatted SD memory card • ALM - Alarm output • V-LOSS - VIDEO signal loss alarm • ERR - Error
Communication interface:	RS-485
Cables description:	CONTROL PANEL / DVR : • White / RS485B • Red / 12 V Output • Green / RS485A • Black / GND To connect, it is necessary to cut off the factory connector and manually make the connection with the appropriate connectors of the recorder
Power supply:	12 V DC
Weight:	0.18 kg
Dimensions:	• 57 x 35 x 20 mm • 4 m - Length of the cable
Guarantee:	2 years

PRESENTATION

Front panel:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Top view:



In the kit:



Cooperation with the recorder is possible after activating the option in the recorder menu (Menu > Peripherals > Serial) - the activated function is marked in green:

SERIAL DEVICE SETUP		
	COM01	COM02
Serial Dev	Intercom	LRD IC
Baudrate	57600	9600
Data Bit	8	8
Stop Bit	1	1
Check	None	None
MCU COM1:	PANEL	
Baudrate	19200	
SAVE		

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------