

Code: APTI-W22H2-TUYA

IP CAMERA **APTI-W22H2-TUYA** Wi-Fi - 720p 3.6 mm

Net: **19.36 EUR** Gross: **19.36 EUR**

The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The Wi-Fi module used in the device allows the device to operate also in places with limited wiring possibilities.

Attention! Camera for indoor use only. Devices cooperating with the Tuya platform do not have a WEB interface. The camera works only with the mobile application (the camera does not work with recorders). Controlling the device and schedule settings is possible if the device has access to the Internet.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/4 " CMOS
Matrix size:	0.9 Mpx
Resolution:	1280 x 720 - 720p
Lens:	3.6 mm
View angle:	90 ° (manufacturer data)
Range of IR illumination:	5 m
Audio:	• Microphone built-in, • Speaker built-in, • Audio transmission via network, • Bi-directional audio streaming support
Image compression method:	H.264+
Main stream frame rate:	15 fps @ 720p
Network interface:	Wi-Fi - IEEE 802.11 b/g/n
ONVIF:	—
WEB Server:	—
Mobile phones support:	Access by a cloud (P2P) • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Default IP address:	DHCP

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	• Wi-Fi module - IEEE 802.11 b/g/n, • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image • Motion Detection, • Sound signaling, • Video PUSH personal messaging • Access by a cloud (P2P) • micro USB socket • RESET button
Power supply:	• 5 V DC / 0.5 A - via USB port
Power consumption:	max. 2.5 W
Housing:	Plastic
"Index of Protection":	—
Weight:	0.04 kg
Dimensions:	• 65 x 58 x 34 mm • 1 m (cable length)
Supported languages:	English
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Small dimensions camera:



Front view:



Rear view:



Bottom view (power socket):



Memory card slot:



In the kit:



OUR OPINIONS



- Small dimensions of the camera.



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

