

Code: TL-WR902AC

ROUTER TL-WR902AC 2.4 GHz, 5 GHz 300 Mbps + 433 Mbps TP-LINK

Net: 39.05 EUR Gross: 39.05 EUR

The TL-WR902AC mini-size router is ideal for home and travel use. Simple and easy installation and operation. The versatile USB port allows you to share files and connect a 3G/4G modem.

With 433 Mbps wireless speeds over the crystal clear 5 GHz band and 300 Mbps over the 2.4 GHz band, TL-WR902AC offers you the flexibility of 2 dedicated networks and ensures amazing wireless performance. Due to 5 operation modes, the TL-WR902AC is an extremely versatile device.

The TL-WR902AC ensures advanced access control and QoS, its DHCP server supports static assignment of IP addresses.



SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	2 x Integrated, Internal antenna
Standards:	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Baud rates:	300 Mbps + 433 Mbps
LAN ports:	1 x 10/100 Mbps (RJ-45)
LED indicators:	Power, INTERNET, Wi-Fi, USB, WPS
Receiver sensitivity:	2.4 GHz : • 11g 54M : -76 dBm • 11n HT20 MCS7 : -74 dBm • 11n HT40 MCS7 : -71 dBm 5 GHz : • 11a 54M : -76 dBm • 11ac VHT20 MCS8 : -70 dBm • 11ac VHT40 MCS9 : -65.5 dBm • 11ac VHT80 MCS9 : -61.5 dBm
Transmitter power:	< 20 dBm @ 2.4 GHz < 23 dBm @ 5 GHz
DDNS:	• No-IP • Comex • DynDNS
DHCP server:	✓
Firmware update:	✓
Operation modes:	• Router, • AP, • Range Extender, • Client, • WISP

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


Protections:	• WEP, WPA/WPA2 • SPI network firewall • Access control • IP-MAC Binding
Management interface:	Web browser, TP-LINK Tether
Main features:	• IPv4/IPv6 • parental control • Internet access filtering • WAN : Fixed, or dynamic IP address / PPPoE / PPTP / L2TP • QoS - mechanisms, which provide the high quality of transmission • Port forwarding : Virtual Server, Port Triggering, UPnP, DMZ • IPTV - IGMP • DHCP : DHCP server, DHCP client list • FTP server • RESET button • Mode button • Port USB 2.0 • micro USB connector (power)
Power supply:	• 5 V DC / 2 A (power adapter included) • from USB port
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.068 kg
Dimensions:	74 x 67 x 22 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

PRESENTATION

Top view:



Connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------