

Code: RBL41G-2AXD

# ACCESS POINT **RBL41G-2AXD** hAP ax lite Wi-Fi 6 2.4 GHz 574 Mbps MIKROTIK

Net: **62.22 EUR** Gross: **62.22 EUR**

The RBL41G-2AXD access point broadcasts the Wi-Fi 6 generation wireless network in the 2.4 GHz band. Modern technology, affordable price and scalability of the system make the device perfect for use at home, in the office, and, for example, in a hotel.

In addition, thanks to its small sizes and ease of use, the device is a great travel companion, allowing you to avoid using the guest network if only the hotel room has a wired interface for connecting to the Internet.



## SPECIFICATION

|                       |                                                                                                                                                                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency range:      | 2.4 GHz                                                                                                                                                                                                                              |
| Antenna type:         | 2 x Internal antenna                                                                                                                                                                                                                 |
| Standards:            | IEEE 802.11ax/n/b/g                                                                                                                                                                                                                  |
| Baud rates:           | 574 Mbps                                                                                                                                                                                                                             |
| LAN ports:            | 3 x 10 / 100 / 1000 Mbps LAN<br>1 x 10 / 100 / 1000 Mbps Uplink                                                                                                                                                                      |
| LED indicators:       | Power, User, 3 x Ethernet, WAN                                                                                                                                                                                                       |
| Receiver sensitivity: | <ul style="list-style-type: none"><li>• 1M : -100 dBm</li><li>• 11M : -100 dBm</li><li>• 6M : -95 dBm</li><li>• 54M : -77 dBm</li><li>• MCS0 : -95</li><li>• MCS7 : -75</li><li>• MCS9 : -69 dBm</li><li>• MCS11 : -61 dBm</li></ul> |
| DDNS:                 | ✓                                                                                                                                                                                                                                    |
| DHCP server:          | ✓                                                                                                                                                                                                                                    |
| Firmware update:      | ✓                                                                                                                                                                                                                                    |
| Operating system:     | MikroTik RouterOS                                                                                                                                                                                                                    |
| Management interface: | Web browser                                                                                                                                                                                                                          |

|                       |                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Transmitter power:    | max. 22 dBm                                                                                                                              |
| Power supply:         | • 5 V DC / 2.4 A (power adapter included)                                                                                                |
| Main features:        | <ul style="list-style-type: none"> <li>• Wi-Fi 6</li> <li>• Built-in 4-port switch</li> <li>• Port USB</li> <li>• Mode button</li> </ul> |
| Operation temp:       | -40 °C ... 70 °C                                                                                                                         |
| Weight:               | 0.22 kg                                                                                                                                  |
| Dimensions:           | 124 x 96 x 53 mm                                                                                                                         |
| Manufacturer / Brand: | MikroTik                                                                                                                                 |
| Guarantee:            | 2 years                                                                                                                                  |

## PRESENTATION

Front panel:



Rear view:



Top view:



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|

