

Code: RG-EW3200GXPRO

ROUTER **RG-EW3200GXPRO** Wi-Fi 6, 2.4 GHz, 5 GHz 800 Mbps + 2402 Mbps REYEE

Net: **151.94 EUR** Gross: **151.94 EUR**

With 2402 Mbps wireless speeds over the crystal clear 5 GHz band and 800 Mbps over the 2.4 GHz band, RG-EW3200GXPRO offers you the flexibility of 2 dedicated networks and ensures amazing wireless performance. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band - all at the same time.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes. 4 external antennas provide stable omnidirectional signal and superior wireless coverage.



SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	8 x Omnidirectional antenna - Integrated : • 6 dBi @ 5 GHz 4x4 MU-MIMO • 5 dBi @ 2.4 GHz 4x4 MU-MIMO
Standards:	IEEE 802.11 b/g/n @ 2.4 GHz , IEEE 802.11 a/n/ac/ax @ 5 GHz
Baud rates:	800 Mbps + 2402 Mbps
LAN ports:	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink
LED indicators:	Status, Mesh
DDNS:	✓
DHCP server:	✓
Firmware update:	✓
Protections:	WPA/WPA2 Support DoS defence
Management interface:	Web browser, Configuration using the Reyee Router application
Mobile phones support:	Android: Free application Reyee Router iOS (iPhone): Free application Reyee Router
Transmitter power:	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Power supply:	12 V DC / 2.5 A (power adapter included)
Power consumption:	≤ 36 W
Main features:	• Support for Reyee Mesh technology, • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Static / dynamic routing • Built-in 4-port switch • Access Point • QoS • Remote management • DMZ • UPnP • Support for dynamic ARP mapping and static table • Port forwarding • Port Mapping • parental control • Guest Network - a separate and secure network for guests • DHCP client list • SSID hiding • IPv6 compliance • PPTP VPN Server / Client
Operation temp:	0 °C ... 45 °C
Permissible relative humidity:	5 % ... 95 % (non-condensing)
Weight:	0.77 kg
Dimensions:	230 x 230 x 162 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	2 years

PRESENTATION

Front panel:



Device connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------