

Code: RG-EST350-V2

WIRELESS WI-FI BRIDGE **RG-EST350-V2** Wi-Fi 5, 5 GHz REYEE

Net: **277.70 EUR** Gross: **277.70 EUR**

The RG-EST350-V2 wireless bridge allows you to create a stable Wi-Fi connection between two points located at a distance of max. 5 km from each other. The device can be used, for example, in CCTV networks to install IP cameras in places where it is difficult to connect an Ethernet cable (e.g. elevators, construction sites, factory halls, warehouses).

Thanks to the antenna with 15 dBi gain, high output power of the transmitter equal 26 dBm and high sensitivity of the receiver, the device allows to create long-range, stable and efficient wireless connections. Device allows to secure data transmission using the encryption protocols: WPA-PSK/WPA2-PSK/WPA-WPA2-PSK.



SPECIFICATION

Frequency range:	5 GHz : 5.150 GHz ... 5.350 GHz , 5.470 GHz ... 5.725 GHz , 5.725 GHz ... 5.850 GHz
Antenna type:	2x2 MU-MIMO
Gain :	15 dBi
Polarization:	vertical/horizontal
Standards:	IEEE 802.11 a/n/ac
Baud rates:	max. 867 Mbps
Wireless transmission range:	max. 5 km
Operation modes:	Bridge (Point-to-Point), Station (Point-to-Multipoint)
Protections:	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK
LAN ports:	• 1 x 10/100/1000 Base-T LAN 1 + Passive PoE • 1 x 10/100/1000 Base-T LAN 2
Management interface:	Web browser, Ruijie Cloud Central Management System Configuration using the Ruijie Reyee application
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Transmitter power:	max. 26 dBm
Horizontal beam width (H):	31 °
Vertical beam width (V):	14 °
Housing:	Outdoor, plastic (Weatherproof) - IP54
Overvoltage protection:	6 kV lightning

Power supply PoE:	Passive PoE - 24 V DC
Power supply:	• 12 V DC / 0.8 A, • 24 V DC / 0.5 A Passive PoE
Power consumption:	≤ 9 W
Operation temp:	-30 °C ... 65 °C
Permissible relative humidity:	10 % ... 90 %
Memory:	128 MB DDR2, 8 MB Flash
Main features:	• MIMO technology - increases the throughput of wireless link (multiple antennas transmission) • Adjustable transmission power • Transmission range even up to 5 km • Ruijie Cloud Central Management System • Wireless signal quality indicators • SSID hiding • SSH • RESET button
Weight:	0.5 kg
Dimensions:	230 x 132 x 48 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	2 years

PRESENTATION



Mounting side view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connectors:

