

Code: TL-WA854RE

REPEATER **TL-WA854RE** 300 Mbps

Net: **14.86 EUR** Gross: **14.86 EUR**

The TL-WA854RE Repeater is designed for increase the range and power of the signal of existing wireless network.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes.



SPECIFICATION

Frequency range:	2.4 GHz ... 2.4835 GHz
Antenna type:	2 x Indoor
Standards:	IEEE 802.11 b/g/n
Baud rates:	300 Mbps
Modulation type:	DBPSK, DQPSK, CCK, OFDM, 16-QAM 64-QAM
Ethernet interface:	—
LED indicators:	RE Wireless Power The strength of receiving signal of the wireless network
Min. illumination:	• 270M: -68dBm@10% PER • 108M: -68dBm@10% PER • 54M: -76dBm@10%PER • 11M: -85dBm@8% PER • 6M: -88dBm@10% PER • 1M: -90dBm@8% PER
DDNS:	—
DHCP server:	✓
Firmware update:	✓
Operation mode:	Repeater
Protections:	WEP 64/128-bit, WPA-PSK/WPA2-PSK
Number of LAN ports:	—
Managemet interface:	Web browser

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Transmitter power:	< 20 dBm
Power supply:	230 V DC
Power consumption:	3 W
Operation temp. / Relative humidity:	0 °C ... 40 °C / 95 % (non-condensing)
Main features:	• The device has very small dimensions • Plug & Play
Weight:	0.09 kg
Dimensions:	110 x 66 x 75 mm
Guarantee:	2 years

PRESENTATION





Bottom view:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------