

Code: TC-C320N SPEC:I3/E/Y/2.8MM

IP CAMERA TC-C320N SPEC:I3/E/Y/2.8MM - 1080p 2.8 mm TIANDY

Net: 47.07 EUR Gross: 47.07 EUR

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

The AK (analog killer) series camera uses advanced 3DDNR technology and image processing algorithms developed by Tiandy that provide better noise reduction, wide dynamic color reproduction and provides better images at night. AK products are distinguished by five advantages: very good performance, full functionality, cost effectiveness, ease of installation and safety.



SPECIFICATION

Standard:	IP
Resolution:	1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor:	1/3 " Progressive Scan CMOS
Lens:	2.8 mm
View angle:	100 °
Range of IR illumination:	30 m
Memory card slot:	—
Image compression method:	S+265 / H.265 / H.264
Alarm inputs / outputs:	—
Audio:	• Microphone built-in • Audio transmission via network
Main stream frame rate:	25 fps @ 2 Mpx
Interface:	10/100 Base-TX (RJ-45)
WEB Server:	Built-in
Max. number of on-line users:	1
ONVIF:	✓
Mobile phones support:	—

Default IP address:	DHCP or 192.168.1.2
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
Port ONVIF:	80
Main features:	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate • Privacy zones • Motion Detection
Power supply:	PoE (802.3af)
Power consumption:	≤ 6 W
Housing:	Dome - Metal + Plastic
Color:	White
"Index of Protection":	—
Mechanical protection class:	—
Operation temp:	-30 °C ... 65 °C
Weight:	0.23 kg
Dimensions:	Ø 117 x 96 mm
Supported languages:	English
Manufacturer / Brand:	TIANDY
Guarantee:	3 years

PRESENTATION

Camera view after remove the Dome cover:





Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------