

Code: 24V/3A/GPV

## SWITCHING ADAPTER 24V/3A/GPV

Net: 16.79 EUR Gross: 16.79 EUR

Hermetic power supply in a plastic housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



### SPECIFICATION

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| Adapter type:             | Switching                                                                                                              |
| Power voltage:            | 90 ... 264 V AC                                                                                                        |
| Frequency range:          | 47 ... 63 Hz                                                                                                           |
| Output voltage:           | 24 V DC                                                                                                                |
| Output voltage tolerance: | ± 5 %                                                                                                                  |
| Maximal load:             | 3 A                                                                                                                    |
| Output power:             | 72 W                                                                                                                   |
| Efficiency:               | 86 %                                                                                                                   |
| Number of outputs:        | 1 pcs                                                                                                                  |
| Protections:              | <ul style="list-style-type: none"><li>• Overload</li><li>• Short-circuit</li><li>• Overvoltage</li></ul>               |
| Main features:            | <ul style="list-style-type: none"><li>• Protection class : II</li><li>• Box casing designed to wall mounting</li></ul> |
| Housing type:             | Plastic, Waterproof                                                                                                    |
| "Index of Protection":    | IP67                                                                                                                   |
| Operation temp:           | -30 °C ... 70 °C                                                                                                       |
| Weight:                   | 0.36 kg                                                                                                                |
| Dimensions:               | 162 x 42 x 33 mm                                                                                                       |
| Guarantee:                | <b>3 years</b>                                                                                                         |

### PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



**PACKAGE**

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|