

Code: GV6-24V/3.2A

SWITCHING ADAPTER **GV6-24V/3.2A**

Net: **31.52 EUR** Gross: **31.52 EUR**

Hermetic power supply in a plastic housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



SPECIFICATION

Adapter type:	Switching
Power voltage:	200 ... 240 V AC
Frequency range:	50 / 60 Hz
Output voltage:	24 V DC
Maximal load:	3.2 A
Output power:	75 W
Number of outputs:	1 pcs
Protections:	• Overload • Short-circuit • Overvoltage • Overheat
Main features:	Box casing designed to wall mounting
Housing type:	Metal, Hermetic
"Index of Protection":	IP67
Operation temp:	-40 °C ... 75 °C
Weight:	0.59 kg
Dimensions:	137 x 67 x 37 mm
Guarantee:	3 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------