

Code: AT-UPS800-LED

## UPS **AT-UPS800-LED** 800 VA EAST

Net: **65.08 EUR** Gross: **65.08 EUR**

The AT-UPS800-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.



### SPECIFICATION

|                                          |                                                                                                                                                                      |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nominal power:                           | 480 W                                                                                                                                                                |
| Apparent Power:                          | 800 VA                                                                                                                                                               |
| Input voltage:                           | 162 V ... 295 V AC                                                                                                                                                   |
| Input frequency:                         | 50 / 60 Hz (auto detection)                                                                                                                                          |
| Output voltage:                          | 230 V AC $\pm$ 10 % (Approximated Sine Wave)                                                                                                                         |
| Output frequency:                        | 50 / 60 Hz $\pm$ 1 %                                                                                                                                                 |
| Transfer time:                           | 2 ... 7 ms (typical), max. 10 ms                                                                                                                                     |
| Charging time (recover to 90% capacity): | 8 hours                                                                                                                                                              |
| Battery:                                 | 1 pcs - 12V/8Ah                                                                                                                                                      |
| Estimated battery operation time:        | 10 ... 20 minutes - depending on the load                                                                                                                            |
| Number of outputs:                       | 2 pcs CEE 7/3 (Schuko)                                                                                                                                               |
| Protections:                             | <ul style="list-style-type: none"><li>• Glass Fuse</li><li>• Overvoltage</li><li>• Overload protection</li><li>• Overcharge protection</li><li>• Discharge</li></ul> |
| Operation state indication:              | <ul style="list-style-type: none"><li>• LED diodes,</li><li>• Sound signaling</li></ul>                                                                              |

|                                      |                                                                                                                                                                                                                             |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:                       | <ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Configurable alarm</li> <li>• COLD START: - Cold start of the power adapter</li> </ul> |
| Application:                         | <ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>                                          |
| Housing type:                        | Tower                                                                                                                                                                                                                       |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 20 ... 90 %                                                                                                                                                                                                |
| Weight:                              | 4.84 kg                                                                                                                                                                                                                     |
| Dimensions:                          | 300 x 100 x 142 mm                                                                                                                                                                                                          |
| Manufacturer / Brand:                | EAST                                                                                                                                                                                                                        |
| Guarantee:                           | 2 years                                                                                                                                                                                                                     |

## PRESENTATION

Front view:



Rear view:



#### PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|