

Code: AT-UPS1000RT/2-RACK

UPS AT-UPS1000RT/2-RACK 1000 VA EAST

Net: 406.89 EUR Gross: 406.89 EUR

The AT-UPS1000RT/2-RACK UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device is mounted to RACK 19" cabinet.

The device is a power supply of the online type and provides advanced mode of operation in total separation from the external mains. Thanks to this, it completely isolates connected devices and performs in practice the function of preventive protection against phenomena accompanying dynamic changes in mains parameters. These power supplies generate current transferred from the battery, which is constantly charged.

The device works with power supply adapters having Active Power Factor Correction (APFC).



SPECIFICATION

Power adapter type:	Online
Nominal power:	900 W
Apparent Power:	1000 VA
Input voltage:	230 V AC \pm 25 %
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 5 % (Pure Sine Wave)
Output frequency:	50 / 60 Hz
Voltage adjustment:	\pm 1 %
Frequency adjustment:	—
Transfer time:	4 ms
Charging time (recover to 90% capacity):	4 hours
Battery:	3 x 12V/9Ah
Estimated battery operation time:	<ul style="list-style-type: none">• 35 minutes @ 200 W,• 16 minutes @ 400 W,• 10 minutes @ 600 W,• 6.5 minutes @ 800 W,• 5.5 minutes @ 900 W
Number of outputs:	<ul style="list-style-type: none">• 1 pcs CEE 7/3 (Schuko),• 2 pcs IEC-320 C13
Management software:	UPSmart (Windows, Linux)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Protections:	<ul style="list-style-type: none"> • Glass Fuse • Overvoltage • Overload protection • EPO (Emergency power off) switch
Operation state indication:	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling
Main features:	<ul style="list-style-type: none"> • Auto restart while AC is recovering • The device has a rotating display • Automatic Voltage Regulator (AVR) • "Cold Start" function • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Battery replacement during operation (Hot-swap) • The device works with power supply adapters having Active Power Factor Correction (APFC) • Excellent microprocessor control guarantees high reliability • UPS auto diagnostic system • Battery charge and maintenance control • USB/RS-232 communication port
Application:	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Rack/Tower 2-in-1 Design
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ~ 95 % (non-condensing)
Weight:	14.3 kg
Dimensions:	440 x 88 x 430 mm ; RACK 19", 2U
Manufacturer / Brand:	EAST
Guarantee:	2 years

PRESENTATION

The device has a rotating display:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------