

Code: AT-UPS2000-LED

UPS AT-UPS2000-LED 2000 VA EAST

Net: 160.72 EUR Gross: 160.72 EUR

The AT-UPS2000-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.

The line-interactive power supplies analyse the voltage, frequency and phase shift angle on a current basis, and filter the voltage transmitted to the connected devices. When a mains failure is detected, the UPS immediately switches to autonomous operation mode and continues to power the equipment using the energy accumulated in internal batteries.



SPECIFICATION

Power adapter type:	Line-interactive
Nominal power:	1200 W
Apparent Power:	2000 VA
Input voltage:	145 ... 295 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	220 / 230 / 240 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Voltage adjustment:	—
Frequency adjustment:	—
Transfer time:	8 ms (typical), max. 10 ms
Charging time (recover to 90% capacity):	6 ... 8 hours
Battery:	2 pcs - 12V/9Ah
Number of outputs:	2 pcs CEE 7/3 (Schuko)
Management software:	—
Protections:	• Glass Fuse • Overvoltage
Operation state indication:	• LED diodes, • Sound signaling

Main features:	• Auto restart while AC is recovering • Excellent microprocessor control guarantees high reliability • COLD START function for manual switch to the battery power supply • Automatic Voltage Regulator (AVR) • Automatic battery charging in OFF mode • self test feature
Application:	• network, servers, workstations • Surveillance Systems • small servers, DVRs, telecommunication equipment, VoIP working hardware, desktop computers, etc.
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 5 ... 90 %
Weight:	12.2 kg
Dimensions:	380 x 125 x 225 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------