

Code: AT-UPS3000/3-LCD

UPS AT-UPS3000/3-LCD 3000 VA EAST

Net: 498.61 EUR Gross: 498.61 EUR

The AT-UPS3000/3-LCD UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.

The device is a power supply of the online type and provides advanced mode of operation in total separation from the external mains. Thanks to this, it completely isolates connected devices and performs in practice the function of preventive protection against phenomena accompanying dynamic changes in mains parameters. These power supplies generate current transferred from the battery, which is constantly charged.

The device works with power supply adapters having Active Power Factor Correction (APFC).



SPECIFICATION

Power adapter type:	Online
Nominal power:	2700 W
Apparent Power:	3000 VA
Input voltage:	208 ... 240 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	208 ... 240 V AC $\pm$ 5 % (Pure Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 0.1 Hz
Voltage adjustment:	$\pm$ 1 %
Frequency adjustment:	—
Transfer time:	• 0 ms On-Line • 4 ms (typical) Bypass
Charging time (recover to 90% capacity):	8 hours
Battery:	8 pcs - 12V/7Ah
Estimated battery operation time:	• 28.5 minutes @ 600 W, • 18 minutes @ 800 W, • 11.5 minutes @ 1000 W, • 9 minutes @ 1200 W, • 6 minutes @ 1600 W, • 3.5 minutes @ 2000 W, • 3 minutes @ 2700 W
Number of outputs:	4 pcs CEE 7/3 (Schuko) ,

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Management software:	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)
Protections:	• Short-circuit • Overload protection • Overcharge protection • Discharge • Temperature • EPO (Emergency power off) switch
Operation state indication:	• Large, readable LCD display with backlight : Voltage, Current frequency, Work load, Battery status, Battery charging, Temperature, Fan status, • LED indicators displaying the device's operating status : Operation modes - On-Line, Error, • Sound signaling
Main features:	• Auto restart while AC is recovering • The device works with power supply adapters having Active Power Factor Correction (APFC) • "Cold Start" function • Remote management - UPSmart application included • Excellent microprocessor control guarantees high reliability • Automatic Voltage Regulator (AVR) • Battery charge and maintenance control • USB/RS-232 communication port • SNMP - Option
Application:	• Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	23.8 kg
Dimensions:	419 x 191 x 335 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Large, readable LCD display:



Rear view:





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------