

Code: MOD-SATRIX/DVB-T

MODULATOR DVB-T MOD-SATRIX/DVB-T

Net: 148.34 EUR Gross: 148.34 EUR

The MOD-SATRIX/DVB-T digital modulator allows to put the HD signal (from camera, terrestrial, satellite TV receiver, Blu-ray, DVD player, etc.) from HDMI input to RF OUT output as DVB-T (COFDM), Full HD 1080p standard in VHF/UHF bands.



SPECIFICATION

Inputs:	1 pcs HDMI, Full HD 1080p , 1 pcs RF (F) , 1 pcs USB
Encoding:	H.264 HP@ level 4.1 max. 1080p @ 30 fps
Supported HDMI resolutions:	SD, HD HDMI 1.4a
HDCP compliance:	✓
Output:	1 pcs RF (F)
RF output level adjustment:	86 dBμV, -14 dB ... +6 dB
RF output frequency (channels) range:	174 ... 233 MHz VHF (III) 470 ... 858 MHz UHF
Modulation type:	QPSK, 16-QAM, 64-QAM
Power supply:	12 V DC / 1.5 A (power adapter included)
Main features:	• Firmware upgrade via USB port • Built-in LTE filter • Aspect ratios 4:3, 16:9 • MER > 35 dB • Bitrate max. 31.668 Mbps
Weight:	0.46 kg
Dimensions:	164 x 104 x 41 mm
Guarantee:	2 years

PRESENTATION

Connectors:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Top view:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------