

Code: MHD-001P

MODULATOR DVB-T MHD-001P

Net: 136.41 USD Gross: 167.78 USD

The MHD-001P digital modulator allows to put the HD signal (from camera, terrestrial, satellite TV receiver, Blu-ray, DVD player, etc.) from HDMI input to RF OUT output as DVB-T (COFDM), Full HD 1080p standard in VHF/UHF bands.



SPECIFICATION

Inputs:	<ul style="list-style-type: none">• 1 pcs HDMI, Full HD 1080p• 1 pcs RF (F)
Encoding:	MPEG-4 AVC / H.264
Supported HDMI resolutions:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p @ 24 / 50 / 60 fps
Output:	1 pcs RF (F)
RF output level adjustment:	60 dB μ V ... 90 dB μ V
RF output frequency (channels) range:	174 ... 230 MHz ; 470 ... 862 MHz
Modulation type:	64-QAM
Power supply:	12 V DC / 1 A (power adapter included)
Main features:	<ul style="list-style-type: none">• The channel selection is made using the buttons• The built-in display shows the currently used channel• Adjusting the signal level at the output : 0 ... 30 dB
Weight:	0.17 kg
Dimensions:	133 x 63 x 39 mm
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Top view:



Device connectors:



In the kit:

