

Code: AX-2560F

VGA-VIDEO CONVERTER AX-2560F

Net: 14.93 EUR Gross: 14.93 EUR

The AX-2560F converter allows to connect a VGA video signal (for example from computer) to the TV monitor using AV input (Composite Video signal) or S-Video input.

Device is perfect for presentation purposes, slides shows, where computer image should be presented on bigger monitor or TV-set screen.



SPECIFICATION

Input:	VGA
Output:	Video composite (BNC socket), S-VIDEO, VGA (bypass)
Output signal possible standards:	PAL / NTSC
Supported resolutions:	800 x 600, 1024 x 768, 1280 x 1024, 1366 x 768, 1440 x 900, 1600 x 900, 1600 x 1200, 1680 x 1050, 1920 x 1080, 1920 x 1200, 2048 x 1536, 2560 x 1600
OSD menu:	✓
Possible settings:	• vertical and horizontal size, vertical and horizontal position • brightness, contrast, saturation sharpness, hue • Monitor type correction - LCD/CRT
Power supply:	USB or power adapter 5 V DC (power adapter not included)
Weight:	0.07 kg
Dimensions:	100 x 67 x 26 mm
Guarantee:	2 years

PRESENTATION

Front panel:



Device connectors:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Schematic diagram of converter operation:



1. Monitor with S-Video or CVBS input

2. Monitor VGA

3. Computer

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------