

Code: AX-2560

## VGA-VIDEO CONVERTER AX-2560

Net: 13.38 EUR Gross: 13.38 EUR

The AX-2560 converter allows to connect a VGA video signal (for example from computer) to the TV monitor using AV input (Composite Video signal) or S-Video input. Device is perfect for presentation purposes, slides shows, where computer image should be presented on bigger monitor or TV-set screen.

**Attention!** With the VGA through-connection, you may notice slight deterioration in picture quality.



### SPECIFICATION

|                                   |                                                                                                                                                                                                                                                                                  |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input:                            | VGA                                                                                                                                                                                                                                                                              |
| Output:                           | Video composite (Cinch), S-VIDEO, VGA (bypass)                                                                                                                                                                                                                                   |
| Output signal possible standards: | PAL / NTSC                                                                                                                                                                                                                                                                       |
| Supported resolutions:            | 640 x 480, 800 x 600, 1024 x 640, 1024 x 768, 1280 x 768, 1280 x 800, 1280 x 1024, 1280 x 960, 1360 x 768, 1440 x 900, 1600 x 1200, 1680 x 1050, 1768 x 992, 1792 x 1344, 1800 x 1440, 1920 x 1080, 1920 x 1200, 1920 x 1440, 2048 x 1152, 2048 x 1280, 2048 x 1536, 2560 x 1600 |
| OSD menu:                         | ✓                                                                                                                                                                                                                                                                                |
| Possible settings:                | vertical and horizontal size, vertical and horizontal position<br>brightness, contrast, saturation sharpness, hue<br>Monitor type correction - LCD/CRT                                                                                                                           |
| Power supply:                     | USB or power adapter 5 V DC (power adapter not included)                                                                                                                                                                                                                         |
| Weight:                           | 0.064 kg                                                                                                                                                                                                                                                                         |
| Dimensions:                       | 100 x 62 x 26 mm                                                                                                                                                                                                                                                                 |
| Guarantee:                        | 2 years                                                                                                                                                                                                                                                                          |

### PRESENTATION

Front panel:



Device connectors:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Schematic diagram of converter operation:



1. Monitor with S-Video or CVBS input

2. Monitor VGA

3. Computer

In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|