

CONVERTER TO COMPUTER MONITORS **VGA-1920T**

Input:	• Video composite (BNC socket), • S-VIDEO, • VGA (bypass)
Input signal possible standards:	• PAL, NTSC, • VGA (bypass)
Output:	VGA (bypass)
Supported resolutions:	• 4:3 800x600 @ 60/75 Hz 1024x768 @ 60 Hz 1280x1024 @ 60 Hz 1600x1200 @ 60 Hz • 16:9 / 16:10 1280x720 @ 60 Hz 1360x768 @ 60 Hz 1440x900 @ 60 Hz 1680x1050 @ 60 Hz 1920x1080 @ 60 Hz 1920x1200 @ 60 Hz
OSD menu:	✓
Possible settings:	brightness, contrast, saturation, hue - the settings are saved after power off
Power supply:	5 V / 1 A (power adapter included)
Weight:	0.090 kg
Dimensions:	100 x 67 x 27 mm
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60




Device connectors:



Example of device using:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------