

Code: M-207G

SINGLE-MODE MEDIA CONVERTER TXRX SET **M-207G** ULTIMODE

Net: **1 786.07 CZK** Gross: **1 786.07 CZK**

The M-207G converter allows to change the data stream transmission media from standard STP/UTP cable to single-mode fiber cable.
The device is equipped with SC connector ensuring reliable connections. Optical signal is transmitted and received in the II i III transmission window of 1310/1550 nm.



SPECIFICATION

Optical connector type:	SC / PC
Number of fibers:	1 pcs
Transmission range:	20 km - Single-mode fiber
Supported standards:	IEEE 802.3, IEEE 802.3u
Port LAN:	1 pcs (RJ-45. UTP/STP)
Transmission speed:	10 / 100 / 1000 Mbps
Optical wavelength:	1550 / 1310 nm
Main features:	• MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Auto detection of the bit rate • Bi-directional transmission via single fiber • LED indicators showing operating status • Wavelength-Division Multiplexing technology WDM (Tx 1550nm / Rx 1310nm)
Power supply:	5 V DC / 1.2 A (power adapter included)
Operation temp:	0 °C ... 50 °C
Weight:	0.176 kg
Dimensions:	105 x 70 x 26 mm - Transmitter or receiver dimensions
Manufacturer / Brand:	ULTIMODE
Guarantee:	2 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Rear view:



Top view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

