Code: ASA2212A

TIME & ATTENDANCE RECORDER **ASA2212A** DAHUA

Net: 377.44 EUR Gross: 377.44 EUR

The ASA2212A Time Attendance Recorder is standalone device equipped with keypad, RFID reader and fingerprint reader.

Time Attendance Recorder has a memory to store up to 1000 users + 5 administrators and up to 3000 different fingerprints (max 3 for one user). The device enables storing up to 150 000 events, taking into account the programmable work schedule (individual and group) and the distinction of: standard events, overtime, lateness and earlier exits.

The identification of each user can be done using the PIN code consisting of 1 ... 8 digits, a fingerprint or with using the proximity reader working in 13.56 MHz S50 standard. It is also possible to create a user with only one identification method.

SPECIFICATION

FINGERPRINT READER:	
Identification time:	< 1.5 s
FAR (False Acceptance Rate):	≤ 0.00004 %
FRR (False Rejection Rate):	≤ 0.15 %
PROXIMITY READER:	
Cards support:	13.56 MHz S50
Reading distance of prox-keys:	3 ... 8 cm
Keyboard built-in:	Touch control keys
Doorbell button:	–
Relay output:	1 x NO/NC or Outdoor bell
Internal memory:	32 MB
Memory card slot:	Events saving to the micro SD card - 8 GB included

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Main features:	• Autonomous operation • 1000 indexed users, • The built-in camera enables observe the reader's surroundings in real time, • 3000 indexed fingerprints (maximum 3 per user), • Non-volatile log buffer of the last 150 000 events, • LCD display, • It is possible to connect the door release button • The ability to operate as a simple access controller • Sound signaling • Firmware upgrade via USB port • The possibility of programming group or individual work schedules, taking into account the permissible time of lateness and earlier exit • The distinction of standard events, overtime, lateness and earlier exits • Data export to USB flash memory in "*.xls" format • The device can signal when the shift ends with an audible signal
Power supply:	9 ... 15 V DC / 200 mA (power adapter not included)
Weight:	0.37 kg
Dimensions:	192 x 160 x 32 mm
Operation temp:	-5 °C ... 55 °C
Permissible relative humidity:	5 % ... 95 %
Manufacturer / Brand:	DAHUA
Guarantee:	**3 years**

PRESENTATION

Front panel:

Mounting side view:

Connectors:



Bottom view:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg