

Code: DS-1600KI(B)

IP KEYBOARD CONTROLLER **DS-1600KI(B)** Hikvision

Net: **2 188.60 EUR** Gross: **2 188.60 EUR**

The DS-1600KI(B) keyboard is an integral part of the IP monitoring systems proposed by the HIKVISION company. The device allows you to control each of the system components - from individual cameras, through recorders, external video decoders, to the servers of the VMS system and the monitor wall.



SPECIFICATION

Users + admins:	31 + 1
Connectors:	• 1 x RJ-45 - Gigabit Ethernet • 2 x USB 2.0 • 1 x HDMI • 1 x DVI • 2 x Jack 3.5 mm socket - Headphones output, External microphone input
Communication standard:	• Gigabit Ethernet, RJ-45 socket, • Network mode - Wi-Fi
Manipulator:	4-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)
Display:	10.1 " LCD - 1024 x 600 px, capacitive touch screen, with light indication
Video output:	1 x HDMI 1 x DVI
PTZ control:	• IP cameras - Hikvision • Recorders Hikvision • Other elements of the VMS system
Alarm inputs / outputs:	—
Main features:	• Backup to USB drive (pendrive, external drive) • Live image view : 2 x 1080p (for full resolution), 16 x Sub stream • Bi-directional audio streaming support • Large, readable LCD display with backlight • Detachable joystick module allows you to place it in the most ergonomic place for the user • Split screen at view from cameras : 1 / 4 / 8 / 9 / 16 • Graphic menu - touch control or Mouse support
Power supply:	• 12 V DC / 4 A (power adapter included) • 802.3af/at
Power consumption:	≤ 15 W
Operation temp. / Relative humidity:	-10 °C ... 55 °C / 10 % ... 90 % (non-condensing)
Weight:	1.72 kg
Dimensions:	404 x 154 x 180 mm
Supported languages:	English
Manufacturer / Brand:	Hikvision
SAP Code:	302600232

Guarantee:

3 years

PRESENTATION

Front view:



Front panel:



Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

