

Code: KT-708

RS-485 KEYBOARD CONTROLLER **KT-708**

Net: **74.87 USD** Gross: **92.09 USD**



Device enables quick access to the main functions, such as camera zoom and convenient 3D joystick control. Allows to control the most of camera models at direct mode (presets, routes, vectors control, etc.).
The device has very small dimensions.

SPECIFICATION

Protocols:	Pelco-D, Pelco-P, DAHUA, HIK
Baud rates:	2400, 4800, 9600, 19200 38400 bps
Cameras numbers (ID):	0 ... 255
Maximal control distance:	1200 m
Communication standard:	RS-485 RJ-45 socket
Manipulator:	2-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)
Display:	LCD 2x16 characters
Main features:	<ul style="list-style-type: none">• multiple protocols and different cameras speed supported on each channel• Speed Dome cameras, motor units, MotorZoom cameras/lenses support• Admin password• Keypad backlight buttons
Power supply:	12 V DC / 1 A
Operation temp. / Relative humidity:	-10 °C ... 50 °C / max. 90 %
Weight:	0.250 kg
Dimensions:	130 x 136 x 53 mm
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Top view:



Keyboard connectors:



In the kit:



OUR OPINIONS



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

- User friendly and intuitive keyboard interface.
- LCD display with backlight.
- Small dimensions of the device.

