

Code: RC-8600HD-SDI

DVR **RC-8600HD-SDI** STANDARD: HD-SDI, 8 CHANNELS +eSATA

Net: **635.36 EUR** Gross: **635.36 EUR**

Recorder working in HD-SDI - High Definition Serial Digital Interface standard. HD-SDI is the interface used for transmission of uncompressed, unencrypted digital video signals (optionally may include embedded Audio and Time Code). It bases on coaxial cables with BNC connectors, and allows to clear digital signal transmission at HD quality.



SPECIFICATION

Standard:	HD-SDI
Maximal total frame rate:	56 fps @ 1920 x 1080 px, 120 fps @ 1280 x 720 px,
Recording speed adjustment:	1 - 7 fps (1920 x 1080) 1 - 15 fps (1280 x 720) for each channel
Video inputs:	8 pcs BNC SDI
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	8 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	5
Image records resolutions:	1920 x 1080 1280 x 720
Recording modes:	Manual, Sensor, Motion detection, Schedule
Supported hard drives:	2 x 2 TB SATA 2 x 2 TB eSATA
External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive (max. 60 mins AVI) Huge Backup function - native format backup up to 24h
Searching and playback the records:	EZ Search function Timeline search, events search, fast access to the first and the last record. Playback: forward, backward, fast, step
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support:	Port 5445 • Android: Free application iUMS • iOS (iPhone): Free application iUMS
Alarm inputs / outputs:	8 pcs Input / 2 pcs Output
PTZ control:	RS-485 Pelco-D, hcam-700

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Motion Detection:	Split the screen into zones 20x11 motion zones Very good sensitivity after motion detection records detected channels only
Mouse support:	✓
Power supply:	12 V DC / 5 A (power adapter included)
Weight:	3.1 kg
Dimensions:	388 x 355 x 73 mm
Supported languages:	English, Brazilian Portuguese, Portuguese, Chinese Simplified, Croatian, Danish, French, Greek, Spanish, Korean, German Polish, Russian, Thai, Turkish, Italian
Country of origin:	South Korea
Manufacturer / Brand:	NADATEL
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



In the kit:



Image from HD-SDI camera (resolution 720p - 1280x720):

:

Analog camera image (resolution PAL - 768x576):

:

OUR OPINIONS



- Possibility to Live image view via network at 1920x1080 resolution (only for 1 user / 1 camera configuration).

PACKAGE

Dimensions (L x W x H): 0x0x0 mm

Gross Weight: 0 kg

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60