

Code: F/RG6/PRO

COMPRESSION PLUG F/RG6/PRO

Net: 0.28 EUR Gross: 0.28 EUR

The F/RG6/PRO compression plug, apart from high-quality feature, is also characterized by an integrated seal securing the connector against water penetration.



SPECIFICATION

Connector type:	"F" Plug
Attachment of connector elements:	Compression mounting
Application:	Coaxial cable
Dielectric diameter:	max. 4.8 mm
Wire mounting:	—
Cable diameter:	max. 8.0 mm
Shield fastening:	Compression mounting
Watertightness:	✓
Example of application:	• RG6 • Triset113
Main features:	• Watertight connection with cable and "F" connector • Properly compressed connection is highly resistant to break • Very easy and quick assembly • Corrosion resistance • Very low loss in the whole operating band • To crimp use the crimping tool HTL-548 / HT-5082R
Weight:	0.009 kg
Dimensions:	Ø 14.5 mm x 42 mm
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------