Code: F-WKS/ZAC-TRI113 ANGULAR COMPRESSION PLUG **F-WKS/ZAC-TRI113** Net: 0.92 EUR Gross: 0.92 EUR

The F-WKS/ZAC-TRI113 professional compression connector fulfills all recommendations of SCTE (The Society of Cable Telecommunications Engineers) for this kind connectors.

The features of the connector have been specially matched to the TRISET-113 cables. The dimensions are so matched that after compression connector is crimped on the cable sheath with a force so large that break the connector from the cable is impossible and so small that it does not damage the structure of the cable.



SPECIFICATION

Connector type:	"F" Quick plug, Angular plug
Attachment of connector elements:	Compression mounting
Application:	Coaxial cable
Dielectric diameter:	max. 6.5 mm
Impedance:	75 Ω
Wire mounting:	Pressing
Cable diameter:	max. 8.5 mm
Shield fastening:	Compression mounting
Material:	Brass (Nickel-platted)
Watertightness:	*
Example of application:	Triset113
Main features:	 Wide frequency range Very low loss in the whole operating band Perfect matching to the transmission line within the whole operating band Watertightness of connector with cable connection Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric Properly compressed connection is highly resistant to break Many patent-pending solutions To crimp use the crimping tool ZAC/MSR-2K, HT-5082R
Weight:	0.020 kg
Dimensions:	12 x 39 x 24 mm
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-05-01