

Code: DS-7104NI-Q1/4P(D)

NVR **DS-7104NI-Q1/4P(D)** 4 CHANNELS, 4 PoE Hikvision

Net: **201.50 EUR** Gross: **201.50 EUR**

The DS-7104NI-Q1/4P(D) digital recorder is a professional device using in IP surveillance systems. The H.265+ video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 6 Mpx
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	4 Channels - Audio from cameras
Audio inputs:	—
Audio outputs:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Bitrate:	max. 40 Mbps
Supported hard drives:	1 x 6 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Records playback from max. 4 channels in the same time @ 1080p Smart Search function Smart Playback function
Network interface:	1 x RJ-45 10/100 Base-TX
Network functions:	Live image view, Playback the records, Backup the records - iVMS-4200 application The device has the ability to work with the Hik-Connect application for mobile devices
Network protocols:	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP
ONVIF:	✓
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect

Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
RTSP URL:	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/
USB:	2 pcs USB 2.0
Serial port:	—
Alarm inputs / outputs:	—
PTZ control:	IP Speed Dome Cameras
Motion Detection:	✓
Intelligent Image Analysis:	✓
Main features:	IVS analysis : crossing the line (tripwire), intrusion
Mouse support:	✓
IR remote controller in the set:	—
Switch PoE:	4-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at)
Maximum total switch load:	36 W
Power supply:	48 V DC / 1 A (power adapter included)
Power consumption:	≤ 10 W (without HDD)
Operation temp:	-10 °C ... 55 °C
Weight:	0.49 kg
Dimensions:	200 x 202 x 48 mm
Supported languages:	Polish, English
Manufacturer / Brand:	Hikvision
SAP Code:	303618112
Guarantee:	3 years

PRESENTATION

Top view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Rear panel:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------