

Code: BCS-L-NVR0802-A-4KE-8P

## NVR **BCS-L-NVR0802-A-4KE-8P** 8 CHANNELS, 8 PoE BCS Line

Net: **4 306.64 DKK** Gross: **4 306.64 DKK**

The BCS-L-NVR0802-A-4KE-8P digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



### SPECIFICATION

|                                     |                                                                                                                                                                                                                                      |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                                               |
| Supported resolutions:              | max. 8.3 Mpx - 3840 x 2160 px, 4K UHD                                                                                                                                                                                                |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA                                                                                                                                                                                                           |
| Audio support:                      | 8 Channels - Audio from cameras                                                                                                                                                                                                      |
| Audio inputs:                       | 1 pcs CINCH                                                                                                                                                                                                                          |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                                                                          |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264 / MJPEG                                                                                                                                                                                              |
| Supported hard drives:              | 2 x 10 TB SATA                                                                                                                                                                                                                       |
| Recording modes:                    | Manual, Motion Detection, Schedule                                                                                                                                                                                                   |
| Network protocols:                  | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, Alarm Server, IP Search, P2P                                                                                                      |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                                                                       |
| Default admin user / password:      | admin / -<br>The administrator password should be set at the first start                                                                                                                                                             |
| Default IP address:                 | 192.168.1.64                                                                                                                                                                                                                         |
| Web browser access ports:           | 80                                                                                                                                                                                                                                   |
| PC client access ports:             | Port no.: 8000 or access by a cloud (P2P)                                                                                                                                                                                            |
| Mobile client access ports:         | 8000                                                                                                                                                                                                                                 |
| RTSP URL:                           | <ul style="list-style-type: none"><li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li><li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li></ul> |
| Searching and playback the records: | <ul style="list-style-type: none"><li>• Records searching: by time and events type. Records playback: forward, backward, fast, slow</li><li>• Records playback from max. 8 channels in the same time @ 1080p</li></ul>               |
| Bitrate:                            | max. 160 Mbps                                                                                                                                                                                                                        |
| Network functions:                  | <ul style="list-style-type: none"><li>• Web Server built-in</li><li>• CMS application</li><li>• Live image view, Playback the records, Backup the records, remote access</li></ul>                                                   |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ONVIF:                           | ✓                                                                                                                                                                                                                                                                                                                                                                       |
| Mobile phones support:           | Port no.: 8000 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BCS Manager</a><br>• iOS (iPhone): Free application <a href="#">BCS Manager</a>                                                                                                                                                                                                    |
| Alarm inputs / outputs:          | 4 / 2                                                                                                                                                                                                                                                                                                                                                                   |
| PTZ control:                     | IP Speed Dome Cameras                                                                                                                                                                                                                                                                                                                                                   |
| USB:                             | 2 pcs USB 2.0                                                                                                                                                                                                                                                                                                                                                           |
| Motion Detection:                | ✓                                                                                                                                                                                                                                                                                                                                                                       |
| Intelligent image analysis:      | ✓                                                                                                                                                                                                                                                                                                                                                                       |
| Main features:                   | Functions implemented in cooperation between the recorder and cameras that support these functions<br><br>• Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians,<br>• face detection,<br>• SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle<br>• Privacy zones |
| Mouse support:                   | ✓                                                                                                                                                                                                                                                                                                                                                                       |
| IR remote controller in the set: | ✓                                                                                                                                                                                                                                                                                                                                                                       |
| Operation temp:                  | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                        |
| Switch PoE:                      | 8-port PoE Switch built-in, 25.5 W / Channel                                                                                                                                                                                                                                                                                                                            |
| Maximum total switch load:       | 117 W                                                                                                                                                                                                                                                                                                                                                                   |
| Power supply:                    | 230 V AC                                                                                                                                                                                                                                                                                                                                                                |
| Weight:                          | 2.62 kg                                                                                                                                                                                                                                                                                                                                                                 |
| Dimensions:                      | 375 x 327 x 53 mm                                                                                                                                                                                                                                                                                                                                                       |
| Supported languages:             | Polish, English                                                                                                                                                                                                                                                                                                                                                         |
| Manufacturer / Brand:            | BCS Line                                                                                                                                                                                                                                                                                                                                                                |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                          |

## PRESENTATION

Front panel:



Rear panel:



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|