

Code: DS-7608NXI-K2

## NVR **DS-7608NXI-K2** 8 CHANNELS ACUSENSE Hikvision

Net: **298.26 EUR** Gross: **298.26 EUR**

NVR equipped with advanced functions of intelligent image analysis.



### SPECIFICATION

|                                     |                                                                                                                                                                                                                                                                      |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                                                                               |
| Supported resolutions:              | max. 12 Mpx - 4000 x 3000 px                                                                                                                                                                                                                                         |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA<br>There is a possibility to configure a SPOT function on one of the output                                                                                                                                                               |
| Audio support:                      | <ul style="list-style-type: none"><li>• 8 Channels - Audio from cameras</li><li>• Bi-directional audio streaming support</li></ul>                                                                                                                                   |
| Audio inputs:                       | 1 pcs CINCH                                                                                                                                                                                                                                                          |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                                                                                                          |
| Image compression method:           | H.265+ / H.265 / H.264 / H.264+                                                                                                                                                                                                                                      |
| Supported hard drives:              | 2 x 10 TB SATA                                                                                                                                                                                                                                                       |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                                                                                                                                                           |
| Network protocols:                  | TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS, ONVIF                                                                                                                                                         |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                                                                                                       |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function<br>Records playback from max. 8 channels in the same time |
| Bitrate:                            | max. 80 Mbps                                                                                                                                                                                                                                                         |
| Network functions:                  | <ul style="list-style-type: none"><li>• Live image view, Playback the records, Backup the records</li><li>• max. 128 on-line users - iVMS-4200 application</li></ul>                                                                                                 |
| ONVIF:                              | ✓                                                                                                                                                                                                                                                                    |
| Mobile phones support:              | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">Hik-Connect</a></li><li>• iOS: Free application <a href="#">Hik-Connect</a></li></ul>                                                        |
| Default IP address:                 | 192.168.1.64                                                                                                                                                                                                                                                         |
| Default admin user / password:      | admin / -<br>The administrator password should be set at the first start                                                                                                                                                                                             |
| Web browser access ports:           | 80, 8000                                                                                                                                                                                                                                                             |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PC client access ports:          | 8000                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Mobile client access ports:      | 8000                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| RTSP URL:                        | <ul style="list-style-type: none"> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li> </ul>                                                                                                                                                                                                                                        |
| Alarm inputs / outputs:          | 4 / 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| PTZ control:                     | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Motion Detection:                | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Intelligent Image Analysis:      | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Main features:                   | <ul style="list-style-type: none"> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• face detection</li> <li>• Comparison of faces with images from the database</li> <li>• Support for up to 16 face databases, including 20 000 face images</li> <li>• Smart search for a person based on a face photo</li> <li>• NVR from the AcuSense series</li> </ul> |
| USB:                             | 2 pcs USB 2.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Mouse support:                   | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| IR remote controller in the set: | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Power supply:                    | 12 V DC / 3.3 A (power adapter included)                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Weight:                          | 1.74 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Dimensions:                      | 385 x 322 x 52 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Supported languages:             | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian                                                                                                                                                                                                                               |
| Manufacturer / Brand:            | Hikvision                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| SAP Code:                        | 303616117                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## PRESENTATION

Front panel:



Rear panel:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



## OUR OPINIONS



- Audio transmission via network.

## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60